



Mini Backbone Knotless Rigging Connector

Nickel plated | Hot forged SAE 4130 steel | Self-chocking
Designed for knotless rigging applications | Ideal for top-down rigging

FEATURES & BENEFITS

- Constructed from hot forged SAE 4130 steel
- Heat treated and hardened for high strength and durability
- Nickel plated finish for corrosion protection
- Eliminates lengthy knot tying
- Vital link in fast paced, secure rigging scenarios
- Improves productivity
- Use to lower multiple limbs at the same time
- Aids in balancing limbs over obstacles
- Compatible with arborist rigging ropes of three strand, double braid, or solid braid in conjunction with Nylon/Dyneema loop runners, lifting slings or other rope slings
- Recommended to use with lowering devices such as Portawrap, GRCS (Good Rigging Control System), Hobbs Device, and alternative rigging bollards



PERFECT FOR
SMALLER LIMBS
AND TREES



CHECK
OUT VIDEO
ONLINE!

6.65" IN
LENGTH

ITEM #	36681
MAX ROPE	9/16 in
TENSILE	37,000 lbs
WLL	3,700 lbs
LENGTH	6.65 in
WIDTH	4.1 in
WEIGHT	1.47 lbs
MSRP	\$44.99
UPC	854379006862

062119NBB

NotchEquipment.com
Questions? Contact Your Local Sales Rep

